

**CTEZED 25 HV** on IVECO

↑ 25 m

→ 12 m

👤👤 250 kg

# Versatility and safety at their best.

Ease to use.  
Control.  
Technology.



## CTEZED 25 HV on IVECO

25 m working height, 12 m outreach, S<sup>3</sup> EVO:  
ZED 25 HV sets new standards in its class.



S<sup>3</sup> EVO



Stability  
at height



Impressive 250 kg  
basket capacity



Zero tailswing

### TECHNICAL DATA

- » Double pantograph + telescopic boom with two extensions
- »  $\pm 320^\circ$  turret rotation
- » Smooth proportional simultaneous controls with acceleration and deceleration ramps
- » Engine start and stop from basket and ground controls
- » Automatic engine rpm management
- » Anti-slip aluminium deck
- » All aluminium basket 1400x700x1100 mm
- »  $90^\circ + 90^\circ$  hydraulic basket rotation
- » Master-slave basket levelling
- » 4 hydraulic outriggers with ground pressure sensors: stepless front variable jacking outriggers and rear straight down stabilizers
- » Stepless variable stabilisation managed by S<sup>3</sup> EVO
- » Levelling capabilities up to 3%
- » CAN BUS electronic management system
- » Ground control station (wired console, optional)
- » Load cell
- » Diagnostic display
- » Hydraulic system operated by vehicle's PTO
- » Buzzer indicating PTO engaged
- » Hour meter
- » 230 V AC in the basket
- » EN 280:2015 CE certified
- » Standard boom colours blue (RAL 5017) and white (RAL 9003)




watch the video

**STRENX™**  
PERFORMANCE STEEL






250 KG BASKET PAYLOAD



INTUITIVE USER EXPERIENCE




CTE CONNECT  
SYSTEM INTEGRATED




DIAGNOSTIC AND  
SERVICE DISPLAY




## OUTRIGGER FOOTPRINT




## WORKING ENVELOPE



## DIMENSIONS



### Min Stab




	<b>25* m</b>		<b>1,4 x 0,7 x 1,1 m</b>
	<b>23* m</b>		<b>12* m</b>
	<b>250 kg</b>		<b>GVW min 3.500 kg</b>

\* outreach and height max values and repeatability can change within  $\pm 3\%$  due to manufacturing variation and working condition.

Product specifications are subject to change without notice or obligation. Technical features and drawings in this brochure are for illustrative purposes only \_ZED 25 JHV - ed. 06/21



## Articulated truck-mounted platforms range from 20 m to 32 m



- ★ Most versatile boom configuration
- ★ Most compact machine in its class
- ★ Clean top boom
- ★ Friendly to use intuitive controls
- ★ Easy maintenance
- ★ Excellent boom rigidity during operation



**We are CTE, one of the largest  
european groups in the field of  
lifting people and handling of material.**



**After sales  
assistance**



**Service  
spare parts**



**Scheduled  
maintenance**



**On-site  
assistance**



**Authorized  
workshops**

Efficient services, innovative technical solutions, timely assistance, professional advice and training: 'Work Becomes Easy' is all this. A style, a philosophy at the heart of which are our customers, their safety, their quality of life. For this reason there is a group in CTE united by ideas, motivation and passion to simplify the work of companies active in the lifting of people and objects.



**CTE s.p.a.**  
Via Caproni, 7  
38068 Rovereto (TN)

**Factory**  
Loc. Terramatta, 5  
37010 Rivoli Veronese (VR)

Tel. +39 0464 48.50.50  
info@ctelift.com  
www.ctelift.com



UNI EN ISO 9001:2008 IT 61659